

Single 2-input AND Gate

General Description

The ETQ74LVC1G08 is a single 2-input AND Gate operating from a 1.65V to 5.5V supply. This device is fabricated with advanced CMOS technology to achieve ultra-high speed with high output drive.


Features

- Designed for 1.65V to 5.5V V_{CC} Operation
- Over-voltage Tolerant Inputs
- 24mA Balanced Output Sink and Source Capability
- Near Zero Static Supply Current Substantially Reduces System Power Requirements
- These Devices are Pb-Free and are RoHS Compliant
- Multiple Package Options Automotive AEC-Q100 Grade 1 Qualified
 - Ambient temperature range of -40°C to $+125^{\circ}\text{C}$
 - ESD HBM 4KV PASS
 - ESD CDM 1KV PASS
 - Latch Up Current to 100mA PASS

Device Information

Part No.	Package	Packing Option	MSL
ETQ74LVC1G08	SC70-5 (1.3mm×2.1mm)	Tape and Reel, 3K	1
ETQ74LVC1G08T	SOT23-5 (1.6mm×2.9mm)	Tape and Reel, 3K	3
ETQ74LVC1G08Y	DFN6 (1.0mm×1.5mm)	Tape and Reel, 3K	1

Pin Configuration



ETQ74LVC1G08

Pin Function


SC70-5/ SOT23-5

Pin No.	Pin Name	Function
1	A	Input A
2	B	Input B
3	GND	Ground
4	Y	Output
5	VCC	Supply Voltage

DFN6

Pin No.	Pin Name	Function
1	A	Input A
2	B	Input B
3	GND	Ground
4	Y	Output
5	NC	No connect
6	VCC	Supply Voltage

Block Diagram



Functional Description

Function Table

Input		Output
A	B	Y
L	L	L
L	H	L
H	L	L
H	H	H

ETQ74LVC1G08

Absolute Maximum Ratings

Symbol	Parameter		Value	Unit
V _{CC}	DC Supply Voltage		-0.5 to 7.0	V
V _I	DC Input Voltage ⁽¹⁾		-0.5 ≤ V _I ≤ +7.0	V
V _O	DC Output Voltage Output in Higher or Low State		-0.5 to V _{CC} + 0.5	V
I _{IK}	DC Input Diode Current	V _I < GND	-50	mA
I _{OK}	DC Output Diode Current	V _O < GND, V _O > V _{CC}	±50	mA
I _O	DC Output Sink Current		±50	mA
I _{CC}	DC Supply Current per Supply Pin		±100	mA
I _{GND}	DC Ground Current per Supply Pin		±100	mA
T _{STG}	Storage Temperature Range		-65 to 150	°C
T _L	Lead Temperature, Soldering 10 Seconds		260	°C
T _J	Max Junction Temperature		150	°C
V _{ESD}	ESD Classification	Human Body Model ⁽²⁾	±4000	V
		Charged Device Model ⁽³⁾	±1000	
I _{LU}	Max Latch up Current Above V _{CC} and GND at 125°C ⁽⁴⁾		±100	mA

Stresses exceeding those listed in this table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

Note1: IO absolute maximum rating must be observed.

Note2: HBM tested per AEC-Q100-002(EIA/JESD22-A114);

Note3: CDM tested per AEC-Q100-011(EIA/JESD22-C101);

Note4: Latch up Current Maximum Rating tested per AEC-Q100-004(EIA/JESD78E).

Thermal Characteristics

Symbol	Package	Ratings	Value	Unit
R _{θJA}	SC70-5	Thermal Characteristics, Thermal Resistance, Junction-to-Air	300	°C/W
	SOT23-5		250	
	DFN6(1.0×1.5)		440	
R _{θJB}	SC70-5	Thermal Characteristics, Thermal Resistance, Junction-to-board	75	mW
	SOT23-5		65	
	DFN6(1.0×1.5)		270	
P _D	SC70-5	Power Dissipation in Still Air at 85°C	215	
	SOT23-5		260	
	DFN6(1.0×1.5)		150	

ETQ74LVC1G08

Recommended Operating Conditions

Symbol	Parameter		Min	Max	Unit
V _{CC}	DC Supply Voltage Operating		1.65	5.5	V
	Date Retention Voltage Operating		1.5	5.5	
V _{IN}	DC Input Voltage		0	5.5	V
V _{OUT}	DC Output Voltage (High or Low State)		0	5.5	V
T _A	Operating Temperature Range		-40	125	°C
t _r ,t _f	Input Rise and Fall Time	V _{CC} = 2.5 V ± 0.2 V	0	20	ns/V
		V _{CC} = 3.0 V ± 0.3 V	0	10	
		V _{CC} = 5.0 V ± 0.5 V	0	5	

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied.

Electrical Characteristics

DC Electrical Characteristics

Symbol	Parameter	Condition	V _{CC} (V)	T _A = 25°C			-40°C ≤ T _A ≤ 125°C		Unit
				Min	Typ	Max	Min	Max	
V _{IH}	High-Level Input Voltage		1.65 to 1.95 2.3 to 5.5	0.75V _{CC} 0.7V _{CC}			0.75V _{CC} 0.7V _{CC}		V
V _{IL}	Low-Level Input Voltage		1.65 to 1.95 2.3 to 5.5			0.25V _{CC} 0.3V _{CC}		0.25V _{CC} 0.3V _{CC}	V
V _{OH}	High-Level Output Voltage	I _{OH} = -100μA	1.65 to 5.5	V _{CC} - 0.1	V _{CC}		V _{CC} - 0.1		V
		I _{OH} = -3mA	1.65	1.29	1.52		1.29		
		I _{OH} = -8mA	2.3	1.9	2.1		1.9		
		I _{OH} = -12mA	2.7	2.2	2.4		2.2		
		I _{OH} = -16mA	3.0	2.4	2.7		2.4		
		I _{OH} = -24mA	3.0	2.3	2.5		2.3		
		I _{OH} = -32mA	4.5	3.8	4.0		3.8		
V _{OL}	Low-Level Output Voltage	I _{OL} = 100μA	1.65 to 5.5		0.0	0.1		0.1	V
		I _{OL} = 3mA	1.65		0.08	0.24		0.24	
		I _{OL} = 8mA	2.3		0.20	0.3		0.3	
		I _{OL} = 12mA	2.7		0.22	0.4		0.4	
		I _{OL} = 16mA	3.0		0.28	0.4		0.4	
		I _{OL} = 24mA	3.0		0.38	0.55		0.55	
		I _{OL} = 32mA	4.5		0.42	0.55		0.55	
I _{IN}	Input Leakage Current	V _{IN} = 5.5V or GND	0 to 5.5			± 0.1		± 1.0	μA

ETQ74LVC1G08

I_{OFF}	Power Off Leakage Current	$V_{IN}=5.5V$ or $V_{OUT}=5.5V$	0			1.0		10	μA
I_{CC}	Quiescent Supply Current	$V_{IN}=5.5V$ or GND	5.5			1.0		10	μA

AC Electrical Characteristics

$t_r = t_f = 2.5ns$

Symbol	Parameter	Condition	$V_{CC}(V)$	$T_A = 25^\circ C$			$-40^\circ C \leq T_A \leq 125^\circ C$		Unit
				Min	Typ	Max	Min	Max	
t_{PLH} t_{PHL}	Propagation Delay (Figure3 & 4)	$R_L = 1M\Omega$ $C_L = 15pF$	1.65	2.0	12.5	15	2.0	16.5	ns
			1.8	2.0	10.2	12.6	2.0	15	
		$R_L = 1M\Omega$ $C_L = 15pF$	2.5	0.2	6.0	7.7	0.8	10.8	
		$R_L = 1M\Omega$ $C_L = 15pF$	3.3	0.8	5.0	6.5	0.5	9.6	
				1.2	5.6	7.1	1.5	10.2	
		$R_L = 1M\Omega$ $C_L = 15pF$	5.0	0.5	4.4	5.6	0.5	6.1	
		$R_L = 500\Omega$ $C_L = 50pF$		0.8	4.8	6.1	0.8	6.6	

Capacitance Characteristics

Symbol	Parameter	Condition	Typ	Unit
C_{IN}	Input Capacitance	$V_{CC} = 5.5V$, $V_I = 0V$ or V_{CC}	3.5	pF
C_{PD}	Power Dissipation Capacitance (5)	10 MHz, $V_{CC} = 3.3V$, $V_I = 0V$ or V_{CC}	26	pF
		10 MHz, $V_{CC} = 5.5V$, $V_I = 0V$ or V_{CC}	30	

Note5. C_{PD} is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation: $I_{CC(OPR)} = C_{PD} \times V_{CC} \times f_{in} + I_{CC} \times C_{PD}$ is used to determine the no-load dynamic power consumption; $P_D = C_{PD} \times V_{CC}^2 \times f_{in} + I_{CC} \times V_{CC} \times Fig.$




Figure 3. Switching Waveform





Figure 4. Test Circuit

ETQ74LVC1G08

Package Dimension

SC70-5







Recommended Land Pattern

Unit: mm

ETQ74LVC1G08

SOT23-5




Recommended Land Pattern

Unit: mm

ETQ74LVC1G08

DFN6 (1.0×1.5)



Recommended Land Pattern

Unit: mm

Revision History and Checking Table

Version	Date	Revision Item	Modifier	Function & Spec Checking	Package & Tape Checking
1.0	2025-07-30	Official Version	Wang anran	Yang xiaoxu	Liu jiaying